



1X19 Wire - Type 316SS



Nominal Wire Diameter	Type	Approx. Breaking Strength	Approx. Weight/ 100 Ft	Part Number	List Price/Ft
1/16	1X19	466 Lbs.	.9 Lbs.	WS02	0.22
3/32	1X19	1,050 Lbs.	1.9 Lbs.	WS03	0.43
1/8	1X19	1,866 Lbs.	3.5 Lbs.	WS04	0.67
5/32 / 4mm	1X19	2,908 Lbs.	5.5 Lbs.	WS05	0.97
3/16	1X19	4,200 Lbs.	7.7 Lbs.	WS06	1.33
7/32	1X19	5,728 Lbs.	10.2 Lbs.	WS07	1.79
1/4	1X19	7,481 Lbs.	13.5 Lbs.	WS08	2.09
9/32 / 7mm	1X19	9,400 Lbs.	17 Lbs.	WS09	2.65
5/16 / 8mm	1X19	11,676 Lbs.	21 Lbs.	WS10	3.23
3/8	1X19	15,575 Lbs.	30 Lbs.	WS12	4.53
10mm	1X19	16,000 Lbs.	32.8 Lbs.	WSM10	5.37
7/16	1X19	20,000 Lbs.	41 Lbs.	WS14	6.30
12mm	1X19	22,930 Lbs.	47.2 Lbs.	WSM12	8.10
1/2	1X19	26,675 Lbs.	52.1 Lbs.	WS16	8.10
9/16 / 14mm	1X19	32,400 Lbs.	67 Lbs.	WS18	10.62
5/8 / 16mm	1x19	42,000 Lbs.	85.5 Lbs.	WS20	14.46
3/4 / 19mm	1x19	63,400 Lbs.	108 Lbs.	WS24	23.79

7-Strand Wire -Type 316SS



Nominal Wire Diameter	Type	Approx. Breaking Strength	Approx. Weight/ 100 Ft	Part Number	List Price/Ft
1/16	7X7	335 Lbs.	.73 Lbs.	WR02	0.49
3/32	7X19	700 Lbs.	1.7 Lbs.	WR03	0.78
1/8	7X19	1,328 Lbs.	2.9 Lbs.	WR04	0.84
5/32	7X19	2,074 Lbs.	4.5 Lbs.	WR05	1.27
3/16	7X19	2,963 Lbs.	6.5 Lbs.	WR06	1.36
7/32	7X19	4,056 Lbs.	8.6 Lbs.	WR07	1.97
1/4	7X19	5,308 Lbs.	11.0 Lbs.	WR08	2.14
5/16	7X19	8,290 Lbs.	17.3 Lbs.	WR10	3.19
3/8	7X19	11,951 Lbs.	24.3 Lbs.	WR12	4.32


"XXX" Brand Compact Strand Wire - Type 316SS

Sailing Services no longer stocks the Dyform® compact strand wire manufactured by Bridon Int'l. Ltd. We do stock Sta-Lok's unique wedge for Dyform® wire. There are other types of compact strand wire available; we are currently stocking "XXX" compact strand wire that will fit Sta-Lok's "Dyform" wedge. If you are using a compact strand wire that you did not purchase from us you will have to ensure that the "Dyform" wedge will work with your specific brand of compact strand wire. Use the same precaution when installing Norseman or Hi-Mod fittings on compact strand wire. The bore of the wedge must match the outside diameter of the core wire strands or the terminal will not function as designed. Sailing Services will not be responsible for use of non-supplied compact strand wire with Sta-Lok "Dyform" wedges. Please contact us for more information.

Lifeline Wire - White Vinyl Coated Type 316SS



7x7



Nominal Wire Diameter	Wire Type	Approx. Breaking Strength	Approx. Weight/ 100 FT	Part Number	List Price/Ft
1/8 Coated to 3/16	7X7	1,434 Lbs.	3.9 Lbs.	WV0406	0.98
1/8 Coated to 7/32	7X7	1,434 Lbs.	4.1 Lbs.	WV0407	1.17
5/32 Coated to 1/4	7X7	2,211 Lbs.	5.9 Lbs.	WV0508	1.38
3/16 Coated to 1/4	7X7	3,218 Lbs.	8.0 Lbs.	WV0608	2.00
3/16 Coated to 5/16	7X7	3,218 Lbs.	9.2 Lbs.	WV0610	2.05
1/4 Coated to 3/8	7X7	5,728 Lbs.	14.5 Lbs.	WV0812	3.01

Other colors and wire types are available from stock. See web site.

Nominal Wire Diameter	Type	Approx. Breaking Strength	Approx. Weight/ 100 Ft	Part Number	List Price/Ft
2.5mm	1X7D	1,518 Lbs.	2.28 Lbs.	WCM02.5	1.14
3mm	1X7D	2,200 Lbs.	3.28 Lbs.	WCM03	1.60
4mm	1X7D	3,916 Lbs.	5.91 Lbs.	WCM04	2.42
5mm	1X19D	5,368 Lbs.	9.1 Lbs.	WCM05	3.50
6mm	1X19D	7,810 Lbs.	13 Lbs.	WCM06	4.50
7mm	1X19D	10,820 Lbs.	17.4 Lbs.	WCM07	5.41
8mm	1X19D	13,530 Lbs.	23.2 Lbs.	WCM08	6.87
10mm	1X19D	21,490 Lbs.	36.3 Lbs.	WCM10	10.62
12mm	1X19D	31,746 Lbs.	54.2 Lbs.	WCM12	14.25
14mm	1x25D	42,549 Lbs.	77.28 Lbs.	WCM14	16.44

Navtec Nitronic 50 Straightened Rod

Rod Size	Diameter			Minimum Breaking Strength		Approx. Weight/ 100 Ft		Part Number	List Price/ Ft
	Nominal		+/-	kg	lbs	kg/m	lbs/ft		
	mm	in	in						
-4	4.37	0.17	0.00	2,130	4,700	0.12	0.08	NAVR505-004	3.77
-6	5.03	0.20	0.00	2,860	6,300	0.16	0.11	NAVR505-006	4.27
-8	5.72	0.23	0.00	3,720	8,200	0.20	0.14	NAVR505-008	5.17
-10	6.35	0.25	0.00	4,670	10,300	0.25	0.17	NAVR505-010	6.63
-12	7.14	0.28	0.00	5,670	12,500	0.31	0.21	NAVR505-012	7.84
-15	7.52	0.30	0.00	6,460	14,250	0.35	0.24	NAVR505-015	11.67
-17	8.38	0.33	0.00	7,940	17,500	0.43	0.29	NAVR505-017	11.55
-22	9.53	0.38	0.00	10,200	22,500	0.56	0.38	NAVR505-022	13.00
-30	11.10	0.44	0.00	13,600	30,000	0.76	0.51	NAVR505-030	18.20
-40	12.70	0.50	0.00	17,200	38,000	1.00	0.67	NAVR505-040	26.37

Prices and specifications are subject to change without notice

Sailing Services offers Navtec authorized and trained rod heading and re-heading in our complete rigging shop.