

LIFELINE PARTS AND ACCESSORIES

Turnbuckles - Open Body



LTB			
Wire Size	Pin Size	Part Number	Price
1/8	1/4	LTB0408	36.25
3/16	1/4	LTB0608	40.00
1/4	5/16	LTB0810	61.00

Lifeline Turnbuckle - Chrome Bronze
 Classic open, chrome bronze body with 316SS right hand swage stud and left hand T-Bolt. Body length is 4-1/2 inches. Three inches of adjustment and positive locking for length with a cotter ring. Measure from bearing surface of clevis pin. New lifelines are made with turnbuckles 2/3 open for maximum adjustment when set up.

Turnbuckles - Closed Body Tubular



LTBC				
Wire Size	Pin Size	Adj.	Part Number	Price
1/8	1/4	3	LTBC0408	29.50
3/16	1/4	3	LTBC0608	31.41
1/4	5/16	3-3/4	LTBC0810	51.34

Tubular Body in 316SS. Can be supplied with left or right hand stud. Standard body length 4-1/2 inches.

Turnbuckle Replacement Stud



LST				
Wire Size	Thread Diameter	Thread Length	Part Number	Price
1/8	1/4	2-1/4	LST040872*	6.81
3/16	1/4	2-1/4	LST060872*	8.97
1/4	5/16	2-3/8	LST081076*	16.18

*Add R or L for Thread Direction

Type 316SS. Machine swage terminal. Cross drilled for cotter pin or ring. It is important to note the thread direction of your old stud.

Extra Long and Metric Thread Lifeline Studs Available. Call for Details!


"L" prefix on terminals denotes a lifeline terminal. Do not use lifeline terminals for standing rigging!

Trends in Lifelines

There has been a recent trend in lifelines away from PVC coated 7x7 SS wire rope toward bare 1x19 Type 316 SS wire or the even newer (from the racing crowd) Spectra rope. The durability of the PVC coating and the tendency of Type 302/304 SS alloy wire to rust, as well as the quality of end fittings and the method of swaging the fittings on the wire, have sometimes led to lifeline failure. Further, 1x19 construction in type 316 is common in Europe where in some cases vinyl coating is not-allowed due to difficulty in checking for integrity.

If you choose the more traditional white vinyl coated lifeline wire, Sailing Services offers only Type 316 SS wire rope—and our most popular 3/16" wire is coated to a full 5/16" of PVC. If you choose bare wire lifelines, our 1x19 wire has a bright finish and is made from Type 316 stainless steel alloy to insure a clean rust-resistant look. In either case, we will Kearney swage and bed our best quality lifeline terminals on your choice of wire. See page 13 of this catalog for wire rope or page 31 for Spectra, UHM single braid cordage. Check out our web site at www.sailingservices.com or call our sales staff for more information.

Deck Toggle Turnbuckle



Wire Size	Part Number	Price
1/8	LTBCDT0408	28.72
3/16	LTBCDT0608	31.49

Type 316SS. Body length 4-1/2 inches. Used for an adjustable termination of lifelines to deck. Two 1/4" holes spaced 1-5/16" to center of holes.

Deck Toggle



Wire Size	Part Number	Price
3/16	LDT0608	16.58

Type 316SS. Used to terminate lifelines to deck. Two 1/4" holes spaced 1-5/16" to center of holes. Use conversion sleeve for 1/8" wire.

Toggle Jaw - T-style



Wire Size	Pin Size	Part Number	Price
1/8	1/4	LTG0408	12.99
3/16	1/4	LTG0608	16.00
1/4	5/16	LTG0810	19.83

Type 316SS. Used on one end of a lifeline for a non-adjusting attachment to closed eyes on pulpit or deck fittings. Insure that other end of lifeline will reeve through holes in stanchions as this fitting will not disassemble.